AREA LIGHT/ SPACE NEEDLE





















BRITELITE SOLUTIONS, LLC.

WWW.BRITELITESOLUTIONS.COM

PRODUCTS DESCRIPTION I

This Post Top Luminare is a sleek, specification-grade solution for lighting pathways, parking areas, gardens and other ourdoor spaces. It can be specified in 50W, 75W & 100W. It is capable of replacing HID fxtures ranging from 175W - 400W and can be used effciently on pathways as well as parking lots or general areas.

FEATURES I

- Super Bright LED
- 100-277Vac 50/60Hz Universal Voltage Driver
- Wet Location Rated for Outdoor Use
- Replaces HID/MH 175~400W
- 5 Years Limited Warranty

CONSTRUCTION I

Precision die cast aluminum body with heats in king across the fullmodule, enabling a long life span.

- · Fade Resistant Powder Coat Finish
- Toughened Glass Lens
- 2-3/8" or 3" Post Top Tenon

SPECIFICATIONS |

ITEM	SPECIFICATION	M/N: BLSO-XXWCF-6M50K		
GENERAL	Wattage (W)	50	75	100
PERFORMANCE	Lumens (Im)	6,000	9,000	12,000
	Efficiency (lm/W)	120	120	120
	Distribution	Type V		
	Color Temperature	5000K		
	(CCT)			
	CRI	>73		
ELECTRICAL	Power Factor	>0.9		
	Input Voltage	100-277Vac 50/60 Hz		
PHYSICAL	Housing	Die cast aluminium with power coat paint		
	Lens	Toughened glass		
	Operation Temperature	-30 to 50 deg C		
PACKAGE	GW (LBS)	16.75		
	Carton Size	51*51*18 cm (1pc/ctn)		
CERTIFICATION	Certification	ETL/DLC premium		
	Material Usage	RoHS		
	Environment	Outdoor, Wet Location		
	Humidity	5% - 90% RH, non condensing		
	Warranty	5 years		